40

EXAMPLE 9

Example 1 was repeated except that the processing treatment was changed from process A to process F outlined below and similar results to those obtained in example 1 were obtained.

-	Processing '			D1	:- L
	Time	Temp	erature	Replenishment Rate	
Color Development*1	135 sec	36	° C.	320 r	nl/m²
Bleach-Fix	40 sec	36	6° C.	320 г	nl/m²
Stabilizing (1)*2	40 sec	36	5° C.		
Stabilizing (2)*2	40 sec	36	6* C.	320 r	nl/m²
Drying	40 sec	70)° C.		
	[Color D	evelope	r]		
		5	Stock		
		Sc	olution	Rep	lenishe
Hydroxyethylimino-dia	cetic acid	0.5	gram	0.5	gram
Monoethylene glycol		9.0	grams	10.0	grams
Benzyl alcohol		9.0	grams	10.0	grams
Monoethanolamine		2.5	grams	2.5	grams
Sodium bromide		2.3	grams	1.5	grams
Sodium chloride		. 5.5	grams	4.0	grams
N,N-diethylhydroxylan		5.9	grams	6.5	grams
3-Methyl-4-amino-N-et methanesulfonamidoeth		2.7	grams	3.0	grams
3-Methyl-4-amino-N-et. hydroxyethylaniline	hyl-N-	4.5	grams	5.0	grams
Potassium carbonate		30.0	grams	35.0	grams
Fluorescent whitener (stilbene	1.0	gram	1.2	grams
type)					
Pure water to make		1000	ml	1000	ml
р Н		10.30		10.70	

starting from 15 seconds after immersion in the color developer.

*2Stabilizer replenishment with a counter-flow system from stabilizing bath (2) to

stabilizing bath (1).

The pH was adjusted using potassium hydroxide or hydrochloric acid.

[Bleach-Fix Bath]	Stock Solution = Replenisher		
Ammonium thiosulfate	110	grams	
Sodium bisulfite	12	grams	
Ammonium diethylenetriaminepentaacetato ferrate	80	grams	
Diethylenetriamine pentaacetic acid	5	grams	
2-Mercapto-5-amino-1,3,4-thiadiazole	0.3	gram	
Pure water to make	1000	ml	
pH	6.80		

The pH was adjusted using aqueous ammonia or hydrochloric acid.

	[Stabilizer]		
		Stock Solution = Replenisher	
	1-Hydroxyethylidene-1,1-diphosphonic acid	2.7 grams	
f	o-Phenylphenol	0.2 gram	
	Potassium chloride	2.5 grams	
	Bismuth chloride	1.0 gram	
	Zinc chloride	0.25 gram	
	Sodium sulfite	0.3 gram	
	Ammonium sulfate	4.5 grams	
	Fluorescent whitener (stilbene type)	0.5 gram	
	Pure water to make	1000 ml	
	р Н	7.2	

Processing Treatment E Replenishment Time Temperature Rate 290 ml/m^2 Color 90 sec 38° C. Development 45 sec 35° C. 290 ml/m² Bleach-Fix Water Wash (1) 30 sec 35° C. Water Wash (2) 30 sec 35° C. Water Wash (3) 30 sec 35° C. 320 ml/m²

The replenishment of the wash water was carried out by replenishing the water wash bath (3). The overflow from the water wash bath (3) was fed into the water 15 wash bath (2) and the overflow from this bath was supplied to water wash bath (1) to establish a counterflow replenishment system. At this time the photosensitive material carried over 35 ml/m² of solution from the previous bath and so the replenishment rate was 9.1 20 times.

[Color D	eveloper]	
	Stock	
	Solution	Replenisher
Diethylenetriamine pentaacetic	0.5 gram	0.5 gram
1-hydroxyethylidene-1,1- diphosphonic acid	0.5 gram	0.5 gram
Diethylene glycol	8.0 grams	13.0 grams
Benzyl alcohol	12.0 grams	18.5 grams
Sodium bromide	0.7 gram	_
Sodium chloride	0.5 gram	
Sodium sulfite	2.0 grams	2.5 grams
N,N-Diethylhydroxylamine	3.5 grams	4.5 grams
Triethylenediamine(1,4-diazabicyclo[2,2,2]octane)	3.5 grams	4.5 grams
3-Methyl-4-amino-N-ethyl-N-(β-methanesulfonamidoethyl)aniline	5.5 grams	8.0 grams
Potassium carbonate	30.0 grams	30.0 grams
Fluorescent whitener (stilbene	1.0 gram	1.3 grams
type)	_	
Pure water to make	1000 ml	1000 · ml
pН	10.50	10.90

The pH was adjusted using potassium hydroxide or 45 hydrochloric acid.

[Bleach-Fix Bath]			
		k Solution = eplenisher	
Ammonium thiosulfate	100	grams	
Sodium bisulfite	21.0	grams	
Ammonium ethylenediaminetetraacetato ferrate dihydrate	50.0	grams	
Ethylenediamine tetraacetic acid disodium salt, dihydrate	5.0	grams	
Pure water to make	1000	ml	
Н	6.3		

The pH was adjusted with aqueous ammonia or hydrochloric acid.

[Wash Water]

Pure water was used (Stock=replenisher)

In this context pure water signifies tap water from which all cations other than hydrogen ions and all an- 65 ions other than hydroxyl ions had been reduced to concentrations of less than 1 ppm by means of an ion exchange process.